

## Simplifying Ownership

**PROFIT POTENTIAL.** IPSO's Micro-20 microprocessor control translates into 40 to 50% in water savings vs. most electromechanical washers. Multi-level vend pricing increases your store's overall potential profitability, while audit and diagnostic capabilities aid in management.

**HIGH SPIN SPEEDS.** The new IWF line of washer-extractors produces some the industry's highest spin speeds, including up to 165 G-Force on some models. High Gs mean more water removal, lowered dry times and a laundry better equipped to handle greater turn volumes.

**HIGHLY EFFICIENT.** All IWF washer-extractors are equipped with inverter drives, eliminating large electrical current draws when the motor powers up. The inverter's gradual ramp-up in speeds is much more efficient — helping lower a store's utility costs.

**RUGGED RELIABILITY.** Why mess with success? Our welded channel iron construction is the same formula we've used since 1973, ensuring a strong base and years of reliable service for you.

**PEACE OF MIND.** A 3-year parts warranty (5-years on major components) is standard.

**SERVICEABILITY.** In the unlikely event our machine requires service, IPSO technicians easily can access parts from the front and top — meaning less down time.



## Simplifying Customer Satisfaction

**EASY.** Your customers want to get in and out quickly. Our simple controls make sure they do.

**VARIETY.** Offered in seven capacities, there's an IWF model to fit all your customers' needs. Customers appreciate laundries that offer a variety of washer sizes to perfectly match their load requirements.

**WASHABILITY.** We lead the industry with more agitation during the wash cycle than any other brand. The result? Customers get great clean results.



**FLEXIBILITY.** Clients love having the ability to tailor their wash process to the specific load. The clean design of the Micro-20 ensures they can do it easily via nine preset cycle selections.

**TIME SAVINGS.** The high-speed extract cycles of IWF washer-extractors help lower drying times. That means customers are able to speed through the drying process and get out the door faster.

**A CLEAN APPROACH.** We believe laundry is a pretty basic chore, so why complicate it for your clients with confusing controls and activations. IPSO helps your laundry simply get customers in and out faster.

- IWF014 - 14 lb Washer-Extractor
- IWF018 - 18 lb Washer-Extractor
- IWF025 - 25 lb Washer-Extractor
- IWF030 - 30 lb Washer-Extractor
- IWF040 - 40 lb Washer-Extractor
- IWF055 - 55 lb Washer-Extractor
- IWF075 - 75 lb Washer-Extractor



# IWF Series Washer-Extractor Specifications

	IWF014	IWF018	IWF025	IWF030	IWF040	IWF055	IWF075
Capacity - lb (kg)	14 (6.5)	18 (8.2)	25 (11.3)	30 (13.6)	40 (18.5)	55 (24.9)	75 (34.0)
Width - in (mm)	26" (660)	26" (660)	26" (660)	30 11/16" (780)	30 11/16" (780)	33 7/8" (860)	39" (990)
Depth - in (mm)	31 3/8" (797)	31 3/8" (797)	35 5/16" (897)	35 1/2" (900)	39 3/8" (1000)	40 11/16" (1034)	46 5/8" (1184)
Height - in (mm)	41" (1041)	41" (1041)	41" (1041)	47 3/8" (1204)	47 3/8" (1204)	54 3/16" (1376)	55 9/16" (1412)
Cylinder Dimensions							
Diameter - in (mm)	20 7/8" (530)	20 7/8" (530)	20 7/8" (530)	25 9/16" (650)	26 3/4" (680)	29 1/2" (750)	33 7/16" (850)
Depth - in (mm)	11 5/8" (295)	13" (330)	17 5/16" (440)	15 3/4" (400)	19 11/16" (500)	20 7/8" (530)	21 1/8" (537)
Volume - cu.ft. (liters)	2.30 (65)	2.58 (73)	3.35 (95)	4.66 (132)	6.39 (181)	8.26 (234)	10.74 (304)
Door Opening - in (mm)	11 13/16" (300)	11 13/16" (300)	11 13/16" (300)	11 13/16" (300)	15 3/4" (400)	15 3/4" (400)	15 3/4" (400)
Cylinder Speed	Normal Speed						
Extract - RPM	525	525	525	475	465	445	415
G-Force - RPM	82	82	82	82	82	83	82
	Medium Speed						
Extract - RPM	700	700	700	632	659	628	589
G-Force - RPM	145	145	145	145	165	165	165
Wash - RPM	10-50	10-50	10-50	10-50	10-50	10-50	10-50
Drain Size - in (mm)	2" (50)	2" (50)	2" (50)	2" (50)	3" (75)	3" (75)	3" (75)
Water Inlet - in (#)	3/4" (3)	3/4" (3)	3/4" (3)	3/4" (3)	3/4" (3)	3/4" (3)	3/4" (3)
Inverter Drive	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Voltage/Hz/Phase Circuit Breaker - FLA							
(X)	200-240/50-60/1-3 15	200-240/50-60/1-3 15	200-240/50-60/1-3 10	200-240/50-60/1-3 10	200-240/50-60/1-3 15	200-240/50-60/1-3 15	200-240/50-60/1-3 15
(Q)	200-240/50-60/3 15	200-240/50-60/3 15	200-240/50-60/3 20	200-240/50-60/3 40	200-240/50-60/3 50	200-240/50-60/3 50	200-240/50-60/3 50
(P)	380-415/50-60/3 15	380-415/50-60/3 15	380-415/50-60/3 20	380-415/50-60/3 20	380-415/50-60/3 30	380-415/50-60/3 30	380-415/50-60/3 40
(N)	440-480/50-60/3 10	440-480/50-60/3 10	440-480/50-60/3 20	440-480/50-60/3 20	440-480/50-60/3 30	440-480/50-60/3 30	440-480/50-60/3 40
Net Weight - lb (kg)	384 (174)	399 (181)	441 (200)	617 (280)	677 (307)	844 (383)	1177 (534)
Crated Weight - lb (kg)	423 (192)	432 (196)	461 (209)	646 (293)	725 (329)	977 (443)	1287 (584)
Agency Approvals	CE, ETL <sub>US</sub> , ETL <sub>C</sub>	CE, ETL <sub>US</sub> , ETL <sub>C</sub>	CE, ETL <sub>US</sub> , ETL <sub>C</sub>	CE, ETL <sub>US</sub> , ETL <sub>C</sub>	CE, ETL <sub>US</sub> , ETL <sub>C</sub>	CE, ETL <sub>US</sub> , ETL <sub>C</sub>	CE, ETL <sub>US</sub> , ETL <sub>C</sub>

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications are subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2000.

© Copyright 2008 Alliance Laundry Systems LLC

Printed in the U.S.A.

Questions? Contact us at:  
1 800 USA IPSO or www.ipso.com  
1 800 (872-4776)

## Control Options



**MC2 Micro-20** Microprocessor

**Sigma** Microprocessor has the addition of infrared communication.

